

TECHNICAL SPECIFICATIONS

INPUT / OUTPUT SPECIFICATIONS

- Voice / Fax / Numeric Interfaces:
 - POTS or DID lines with Ground Start or Wink.
 - Digital trunks up to 16 T1 inputs.
- Serial protocols include: TAP, TNPP, and SMDI output.
- Internet protocols include: SMTP, SNPP, Web Interface, WCTP and SMPP output, Serial over TCP/IP, and AOL Instant Messenger^(SM).

STANDARD SYSTEM SPECIFICATION / CONFIGURATION

- Physical dimensions: rack 19"W x 7"H x 24"D
 tower 7.5"W x 18"H x 21"D
- Power 120 VAC
- Window 2000 Professional
- Pentium class processor
- Single T1 interface
- 1 Serial port

SYSTEM OPTIONS

- 48 Volt DC power supply
- 2 to 64 Serial ports
- Hard drive Raid
- Redundant power supplies
- CD ReWritable or Tape backup

NOTES

- A dedicated connection to the Internet with a static IP address is required
- An Internet domain name is required. For example, emails can be addressed to "pagerid@pager.yourdomainname.com"
- Messages sent to a subscriber will be sent to all the pagers defined for the subscriber
- Remote access via Symantec pcAnywhere™
- Remote command line access via secure shell (SSH)

